

 CRISTALENS

ARTIS[®] T PLE

HYDROPHOBIC LENS

PRELOADED



- Monofocal
- Toric



MADE IN FRANCE

CE 0459

TECHNICAL SPECIFICATIONS

Lens type	For implantation in the capsular bag
Optic diameter	6.00 mm (from +10.0D to +25.0D) 5.80 mm (from +25.5D to +35.0D)
Overall diameter	10.79 mm (from +10.0D to +25.0D) 10.50 mm (from +25.5D to +35.0D)
Design	One-piece square edge on 360°
Optic design	Monofocal Aspherical with negative spherical aberration to partly correct corneal spherical aberration Toricity and marks on the posterior face, biconvex
Angulation	5°
Material	Hydrophobic CBK 1.8 from Cristalens
Dioptic powers (spherical equivalent)	From +10.0D to +35.0D by 0.5D
Cylinder powers	+0.75D / +1.50D / +2.25D / +3.00D +3.75D / +4.50D / +5.25D / +6.00D
Estimated A-Constant (SRK-T)	119.3 Ultrasound biometry 119.7 Interference laser biometry
Suggested anterior chamber depth (ACD)	5.77 mm Ultrasound biometry 6.03 mm Interference laser biometry
Refractive index	1.54
Sterilization	Ethylene oxide
Injection system	Preloaded system
Recommended incision size	2.0 mm



Toric calculator available on
our website www.cristalens.fr

 **CRISTALENS** www.cristalens.fr

 **CRISTALENS INDUSTRIE**

4 rue Louis de Broglie - 22300 Lannion - FRANCE
Tel +33 (0)2 96 48 92 92 - Fax +33 (0)2 96 48 97 87

